



Major Features

<ul style="list-style-type: none"> • Supports multi client access and Dynamic IP via DHCP 	<ul style="list-style-type: none"> ▪ Remote access via WebViewer, CM3000 and PDA Viewer
<ul style="list-style-type: none"> • Supports Central Management System, CM3000 	<ul style="list-style-type: none"> ▪ Supports one IDE HDD up to 750Gb
<ul style="list-style-type: none"> • 4 channel standalone security digital video recorder with network access 	<ul style="list-style-type: none"> ▪ Fan less low noise design
<ul style="list-style-type: none"> • CCTV or VGA/LCD monitor outputs 	<ul style="list-style-type: none"> ▪ Backup to Pen Drive or External HDD (FAT32 based – up to 32GB)
<ul style="list-style-type: none"> • 1 channel audio input/output 	<ul style="list-style-type: none"> ▪ Exclusive video enhancement tool
<ul style="list-style-type: none"> • Video compression: MPEG4 	<ul style="list-style-type: none"> ▪ Free playback / Backup application software
<ul style="list-style-type: none"> • Sensor trigger recording 	<ul style="list-style-type: none"> ▪ I/O control for sensor and relay
<ul style="list-style-type: none"> • Intelligent auto-skip bad HDD sectors 	<ul style="list-style-type: none"> ▪ Client Remote SDK support
<ul style="list-style-type: none"> • Remote Software Update 	<ul style="list-style-type: none"> ▪ Supports PPPoE

Performance

Product	EB1304NET
Video input	4
VGA output	1
Audio input/output	1
Display Rate (NTSC / PAL)	120 / 100 fps*
Recording Rate (NTSC / PAL)	120 / 100 fps*
Sensor Input	4
Relay Output	1
USB Port	1
TV Output	1

* CIF

* Specifications subject to change without prior notice

Product Specification

- ◆ 4 composite video inputs (BNC connector)
 - ◆ 1 Composite & 1 VGA outputs
 - ◆ Video compression: MPEG4
 - ◆ Video Format: NTSC and PAL
 - ◆ 1 channel audio input/output
 - ◆ Display Resolution:
 - 720 x 480 / 720 x 576 (NTSC/PAL)
 - ◆ Display frame rate:
 - Total 120/100 fps (NTSC/PAL)
 - ◆ Hue/Brightness/contrast/Saturation adjustable
 - ◆ Recording resolution:
 - Full D1: 720 x 480 / 720 x 576 NTSC/PAL)
 - CIF: 360 x 240 / 360 x 288 (NTSC/PAL)
 - ◆ Recording frame rate
 - CIF: 120/100 fps (NTSC/PAL)
 - Full D1: 60/50 fps (NTSC/PAL)
 - ◆ Recording modes:
 - Schedule (00:00~24:00 set by hour)
 - Manual/Sensor/Continuous/Motion
 - ◆ Auto recycle recording
 - ◆ Auto record enabling
 - ◆ Password authentication mechanism
 - ◆ Operating Temperature: 0 ~ 55°C
- ◆ Playback
 - Instant access playback
 - 4096 event lists supported
 - Video search by date/time/event
 - Easy to playback and backup on windows 2000/XP via exclusive playback application
 - Output as AVI files (Support Windows Media Player)
 - Support playback from HDD via USB
 - Repeating A-B playback and backup
 - Enabling quick HDD to HDD backup
 - Support Watermark function for image verification
 - ◆ I/O
 - 4 sensor inputs and 1 relay
 - Sending alert by e-mail on alarm triggered
 - Relay output controls alarm, lock, light, or other devices
 - ◆ Remote Access:
 - CM3000: Supports Central Management System
 - WebViewer: Remote viewing through Internet Explorer
 - PDA Viewer: Mobile remote access anytime, anywhere
 - Remote SDK support
 - ◆ Dimension: (L) 290mm x (M) 180mm x (H) 52mm

AVerMedia®

423 Dixon Landing Road, Milpitas, CA 95035 USA

U.S: (Tel) 1-408-263-3828 (Fax) 1-408-263-8132

Homepage: www.avermedia-usa.com | Email: avtnvd@avermedia-usa.com